

VancoContact™ 2

EXCELLENT HANDLING AND DRIVING COMFORT
 DEVELOPED ESPECIALLY FOR VEHICLES WITH A HIGH BALANCE POINT
 AND FOR TRANSPORTING HEAVY LOADS.



UTQG:	TREAD:	TRACTION:	TEMPERATURE:
ALL SIZES	300	A	A

FEATURES:	BENEFITS:
• New stiff shoulder design	• Delivers excellent traction and low noise
• Optimized design sipe	• Maximizes resistance to hydroplaning
• Stiff tread	• Provides exceptionally long tread life
• Wide circumferential grooves	• Delivers superior all-season performance
• Optimized flat belt contour	• Creates a smooth, stable ride

Vanco™ 4 Season

YEAR-ROUND COMFORT AND DURABILITY
 UNIQUE GROOVE DESIGN AND TREAD PATTERN IMPROVES RESISTANCE
 TO HYDROPLANING AND PROTECTS AGAINST SIDEWALL DAMAGE.



UTQG:	TREAD:	TRACTION:	TEMPERATURE:
ALL SIZES	280	A	A

FEATURES:	BENEFITS:
• Round contact patch	• Improves resistance against hydroplaning
• Solid sidewall rib	• Protects against sidewall damage
• Special shoulder groove design and interlocking tread pattern	• Increases comfort and lowers tire noise

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in) (MEASURING RIM)	APPROVED RIM WIDTHS (in)	TREAD DEPTH (in - 32nds)	REVS PER MILE
--------------	--------	------	--------------------	------------	----------	----------------	--------------------	------------------	------------------	-------------------------------	--	--------------------------	--------------------------	---------------

VancoContact™ 2

15	65	205/65R15	102/100T	C	BSW	04510080000	25.9	9.6	21.2	50	8.3 (5.5)	5.5 - 7.5	10/32	805
		215/65R15	100H		BSW	04510130000	26	11.0	24.3	51	8.7(6.5)	6.0 - 7.5	10/32	802
16	60	215/60R16	99H		BSW	04510100000	26.1	11.6	25.6	51	8.7(6.5)	6.0 - 7.6	10/32	799

Vanco™ 4 Season

15	70	195/70R15	104/102R	D	BSW	04574410000	25.7	12.0	26.4	65	7.9 (6.0)	5.0 - 6.0	13/32	810
		225/70R15	112/110R	D	BSW	04574450000	27.4	14.9	32.7	65	9.0 (6.5)	6.0 - 7.0	13/32	761
16	65	205/65R16	107/105T	C	BSW	04733060000	26.9	17.3		50	8.5 (6.0)	5.5 - 6.5	13/32	775